

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 July 2004 (15.07.2004)

PCT

(10) International Publication Number
WO 2004/059119 A1

(51) International Patent Classification⁷: **E21B 17/01,**
E02B 17/00

(21) International Application Number:
PCT/NO2003/000378

(22) International Filing Date:
11 November 2003 (11.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20026270 27 December 2002 (27.12.2002) NO

(71) Applicant (for all designated States except US): **STATOIL**
ASA [NO/NO]; N-4035 Stavanger (NO).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BONNEMAIRE,**

Basle [NO/NO]; Blåkklokkeveien 32, N-7049 Trondheim (NO). **GUDMESTAD, Ove, Tobias** [NO/NO]; Søyland, N-4365 Nærbø (NO). **LØSET, Sveinung** [NO/NO]; Theodor Petersens vei 2, N-7049 Trondheim (NO).


(74) Agent: **ABC-PATENT, SIVILING. ROLF CHR. B. LARSEN A.S.**; Postboks 6150 Etterstad, N-0602 Oslo (NO).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: **DEEP WATER FLEXIBLE RISER PROTECTION**



(57) Abstract: The invention relates to flexible risers system for transfer of hydrocarbons between a sea bed installation and a vessel (10) floating at the sea surface. The riser (18) is provided with means (20) for protecting the riser (18) from impacts. The protection means (20) covers at least the upper part of the riser (18) and may be retractable to an in-active position. When in operation, the riser protection means (20) is either suspended from the vessel (10) or from a submerged turret buoy, forming part of a mooring system for the vessel (10). At its lower end the protection means (20) is provided with an annular body (22) surrounding the riser (18), the annular body (22) having sufficient weight to provide a downwardly acting force in the riser protection means (20), causing a stretch or a tension in the riser protection means (20).

WO 2004/059119 A1



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report

DEEP WATER FLEXIBLE RISER PROTECTION

The present invention relates to flexible riser systems designed to operate in deeper ice infested waters where it may be necessary to protect parts of but not the entire length of the flexible riser. More particularly, the present invention relates to protection of flexible risers for transfer of hydrocarbons from an installation on the sea bed to a floating vessel in an area exposed to drifting ice. Such a riser may for example, be required for STL loading or transfer of hydrocarbons to or from a floating production platform or vessel in deeper ice infested waters. The invention could also be used in areas where other types of drifting obstacles are present, e.g. drifting nets or drifting timber.

Background for the invention

Oil exploration has moved into deeper arctic waters. Motion of drifting ice is often a crucial problem when designing and planning a production system or an off-take loading and mooring system in ice infested waters. It is imperative to design systems and methods which eliminate the risks for pollution, caused by damage to the equipment due to impact from the drifting ice.

The drifting motion of ice is mainly governed by wind, waves, ocean currents and tidal forces. From analyses for the Eastern Barents Sea, it has been found that on a large time scale the ice drifting motion is clearly stochastic and with the exception of periods with rather straight lined movements, it resembles Brownian motion. Since ice floes are generally large and heavy, the direction and absolute value of their speed cannot change momentarily. Models predict steady motion of the ice, but occasionally the direction of ice drift may change to the opposite direction in roughly half an hour. This is a major concern for a conventional loading concept where the tanker, say 90 000DWT, is staying in the "wake" behind a

platform or a tower extending up above the sea level. If using a submerged loading concept instead in waters subjected to drifting ice, allowing the tanker to "ice-vane", advantages may be achieved.

5 Tests executed in 1997 and 2000 at the Hamburg Ship Model Basin (HSVA), Germany, testing the Submerged Turret Loading system, STL, in frozen seas, showed that under-keel installations may be in contact with ice as soon as the ice conditions worsens (interactions with ice ridges).
10 Hence, the riser has to be protected from this hazard.

Prior art.

US Patent Specification No. 5,820,429 describes an arrangement of a loading/unloading buoy for use in shallow
15 waters wherein a buoy is arranged for introduction and releasable securement in a downwardly open receiving space in a floating vessel. The buoy comprises a bottom anchored centre member for the passage of fluid from or to a transfer line which is coupled to the underside of the
20 center member. The buoy further comprises an outer member which is rotatably mounted on the center member to allow turning of the vessel about the center member when the outer member is secured in the receiving space. The buoy is provided with a bottom support structure which is
25 connected to the center member of the buoy and arranged for support of the buoy at the sea bed when not in use. To the center member of the buoy there are connected a number of mooring lines extending outwards from the buoy a substantial distance along the sea bed. Such a system has
30 an inherent elasticity allowing raising of the buoy from the sea.

Summary of the invention

The object of the invention is to achieve protection
35 for flexible risers employed in ice infested waters, protecting at least the upper part of a riser extending between the sea bed and a floating platform or vessel.

A further object of the present invention is to provide riser and a riser protection means which quickly may be retracted to a submerged, in-operative position, permitting the riser to be quickly disconnected from its connection point on the vessel or platform and possibly retracted to a position on depths where the riser will not be exposed to impact by the drifting ice. Correspondingly, it is an object to achieve a loading system where the loading operation may be quickly aborted and the moored tanker may be quickly released from the mooring and riser system. It is envisaged that the system may also be used for transfer of hydrocarbons to or from a floating platform and equipment mounted on the sea bed.

Furthermore, according to the invention, means for maintaining a downwards stretch and/or tension in the riser protection means is provided, thereby ensuring proper protection of the flexible riser when exposed to impact from ice floes, debris or the like.

In order to ensure the integrity of the riser during operation, and in order to ensure that the riser protection system will protect the riser properly, a special stretching or tensioning device is incorporated into the riser design. According to a preferred embodiment this device could be made in the form of an annular body attached to the lower end of the riser protection system and extending around the flexible riser, suspended from the lower end of the riser protection means, thereby ensuring that the riser protection device is stretched out and tensioned.

The stretching or tensioning device will also act as a damping means on the motion of the riser, if and when the protection means is hit by an ice floe. The stretching and tensioning device will thus have two functions: it will provide the required protection for the flexible riser by ensuring that the protection means is stretched out and it will also function as a damper, limiting the motion of the flexible riser, including the protection

means, should the riser protection interact with an ice floe.

It should furthermore be envisaged that the riser may be considerably exposed to wear and tear in the region
5 where it passes the stretching or tensioning device and that it will be advantageous if the riser is protected by a rubber collar or similar means.

According to the present invention the objects are achieved by means of a riser protection system as further
10 defined in the claims.

Brief Description of the Drawings

The invention will be further described in detail below in connection with an exemplary embodiment with
15 reference to the drawings, wherein:

Figure 1 shows modelled movement of the ice drift, distances in m;

Figure 2 shows a typical prior art loading system;

Figure 3 shows the loading system according to the invention wherein the riser and a STL buoy are connected
20 to a vessel;

Figure 4 shows details of the riser protection means;

Figure 5 shows in more detail the loading system and the riser protection means according to the present
25 invention; and

Figure 6 shows an enlarged vertical section through an embodiment of the stretching and tensioning device according to the invention.

Detailed Description of the preferred Embodiment

Reference is made to the Applicant's co-pending NO Patent Applications Nos. 2002.4584 and 2002.4585, relating to flexible risers designed to operate in ice infested waters. The content of these two publications are hereby
35 included by reference. The two identified applications relate in particular to risers for shallow waters, possibly incorporating a silo at the sea bed in which the

riser is stored when not in use. The complete length of the riser is being protected by means of a protection element in the form of buckets, ensuring the flexibility of the riser. The buckets are stacked on top of each other when the riser is being disconnected and lowered to the sea bed.

Figure 1 shows modelled movements of the ice drift. The increment between each dot on the graph represents a time lapse of 10 minutes. The Figure gives an impression of the movement during a 24-hour period. As indicated on the graph, the model predicts steady motion of the ice. Occasionally, however, the ice drift may change to the opposite direction in roughly half an hour.

In Figure 2 a tanker vessel or a Floating Production Vessel (FPSO) 10 is moored to a fixed platform 11 and fluids are transferred from the platform 11 to the vessel 10 through a flexible hose 12. The flexible hose 12 is suspended from a rotatably arranged loading arm 13. Since the vessel is only moored to the platform, the possibility of collision between the vessel 10 and the platform 11 is large if and when the drifting direction of the ice changes abruptly. In such a case, the loading operation must stop immediately and the tanker 10 must quickly be released from its mooring system.

In order to overcome such problems, a sub sea loading concept is required, reducing the possible interference with the drifting ice, and still allowing the tanker 10 to 'ice-vane' depending on the movement of the drift ice.

Figure 3 shows in principle a preferred embodiment of a loading system according to the invention. As shown in Figure 3, a vessel 10 (or a floating platform) is floating on the sea surface 14. The vessel 10 is equipped with a moon pool 15, and is rotatably moored to the sea bed 16 by means of a plurality of mooring lines 17. A flexible riser 18 extends between the sea bed 16 and the vessel 10. The flexible riser shown in Figure 3 is given a sag bend and a hog bend by means of buoys 28, in order to compensate for

vertical movement imposed by the vessel. At its upper end the riser 18 is connected to a submerged turret buoy 19. At its lower end the riser 18 is connected to a wellhead or manifold 29 on the sea bed 16. The mooring lines 17 are
5 coupled to the submerged turret buoy 19, allowing the vessel to weathervane. Such turret buoy 19 may be of a type as is further detailed in the applicants US Patent Specification No. 5,820,429, the content of which hereby is included by reference. The upper end of the riser 18 is
10 releasable connected to a corresponding pipe line onboard the vessel by means of a swivel joint (not shown).

According to the invention, the riser 18 is protected by a riser protection means 20. According to the embodiment shown in Figures 3, 4 and 5 the upper end of
15 the riser protection means 20 is suspended from the submerged turret buoy 19 by means of a plurality of chains, wires or the like 21. The lower end of the riser protection means 20 is coupled to a stretching or
20 tensioning device 22, having sufficient weight to provide the required downwards stretch or tension in the riser protection device 20. The stretching device may be formed by an annular body surrounding the flexible riser 18.

According to a preferred embodiment of the invention the riser protection means 20 comprises a plurality of
25 hollow, truncated conical elements 23, having a smaller upper diameter and a larger lower diameter or vice versa, ref. Figure 4.

Figure 4 shows main parts of the riser protection means 20. Thus, the figure the protection means comprises
30 a plurality of hollow, upwards truncated, conical elements 23. Each element is open-ended at both ends. The elements 23 are suspended from each other by means of chains or wires 21. The riser extends through the set of elements 23.

35 Such riser protection means 20 will resist dragging and impact loads from ice passing under the keel of the vessel. The design of the elements 23 in the riser

protection means 20, (ref. Figures 3 and 4) will provide the required bending capabilities due to the suspended, separate elements, suspended by wires or chain 21 and will protect the riser from excessive bending.

5 Since the elements 23 are suspended to each other, the elements 23, when the riser protection means 20 is retracted into an inactive position, will be stacked into each other. This allows the riser protection means 20 always to have an adequate length.

10 If the elements 23 are suspended independently of the riser 18 from the vessel or from the STL buoy 19, the riser 18 will heave with the vessel 10 and will to a certain degree slide within the lower element 23.

15 A possible design for the elements 23 is presented in Figure 4. This design may be varied without deviating from the inventive idea and is only shown to give an idea of the function of the elements 23. On the drawing, chains 21 are used to link the elements 23. It should be appreciated however, that wires or other type of links may be used.
20 The drawing suggests further that four chains 21 are used to link the elements 23. It should be appreciated that the number of chains may be varied, as for example three chains may be suitable.

25 As further shown on Figure 4 the wider rim 24 of each element 23 may be provided with a stacking ridge 25 which also includes attachment eyes 26 for the chains 21.

Figure 4 shows further a schematic view of one embodiment of the riser stretching element 22.

30 Figure 5 shows in more detail the riser protection system shown in Figure 3. As shown, the riser 18 is suspended from a STL buoy 19 arranged in the turret on a vessel 10 floating at the sea surface. Further, the riser protection means 10 is suspended from the STL buoy 19 by means of chains 21. The riser 18 is further in the region
35 of the lower end of the riser protection means 20 provided with a rubber collar 27 or similar means. The purpose of the rubber collar 27 is inter alia other to protect the

riser 18 from wear and tear caused by the annular body 22 due to motions caused by waves, sea current, drifting ice and debris or wind. The collar 27 may have any suitable shape or dimensions and may be formed of any suitable material providing wear and tear resistance on the riser 18. The collar 27 provides also a controlled distribution of forces caused by the annular body 22 onto the riser 18.

Figure 6 shows a vertical section through one embodiment of the invention, showing the annular body 22, suspended by chains from the riser protection means 20 (not shown). As shown, the lower internal corner of the annular body 22 is wedged, while a collar 27 is arranged around the riser 18. The purpose of this embodiment is to minimize the possibility of damaging the riser caused by relative moment between the riser 18 and the tensioning device 22.

The annular body 22 may according to one embodiment of the invention be provided with anchor chains or wires 30, increasing the downwardly acting force on the riser protection means 20, thereby improving tension or the stretch in the riser protection means 20.

The riser protection means 20 may, for example, be suspended from the STL buoy 19 also when in an inactive position, detached from the vessel. Alternatively, the riser protection means 20 may be temporarily stored in a stacked position on board the vessel 10, either in conjunction with a turret/moon pool or in conjunction with an arrangement in the bow region of the vessel in case such type of single point mooring systems are used.

For deeper waters, the riser protection means 20 does not need to cover the riser 18 along its entire length, but only the upper part which may be subjected to ice loads. Limiting the riser protection means 20 to cover only the upper part of the riser 18 will allow the system still to be compact when stored on the sea bed 16.

An important advantage of this system is its ability to operate in any ice condition. As long as the vessel 10

and the mooring 17 can withstand the incoming sea ice, so will the riser 18, as partly protected under the vessel 10. The vertical elasticity of the system makes it able to cope with quite heavy seas. This loading system will thus
5 have a very high operability rate.

This transfer system is independent of the methods used for connection to the vessel 10. It is very suitable for the STL system for example, but may also be employed in other systems. It could for example be adapted to be
10 used as a Single Anchor Mooring loading system for light ice infested waters or waters with for example drifting nets or drifting timber.

The loading system according to the invention may be installed in different water depths, preferably for depths
15 exceeding 20 m.

The system described above, incorporating the stretching or tensioning device, could be applied in connection with all types of floating units. It is particularly attractive as an integral part of an STL
20 loading system in deeper water with ice, but it could also be applied as an integral part of any offshore loading system. Furthermore, the system could be applied in connection with a floating production or drilling platform where some means of riser protection would be needed for
25 some or all of the platform risers. It should be noted that the system in principle could also provide protection of the risers against any type of impacts in addition to impacts from ice floes. Such cases could be impact from steep or breaking waves, floating debris (like timber),
30 some protection in case of impact from ships will also be provided.

C l a i m s

1. A flexible riser or loading system for transferring hydrocarbons between a sea bed installation (29) and a vessel (10) floating at sea surface (14),
5 c h a r a c t e r i z e d i n t h a t the riser (18) is provided with means (20) for protecting the riser (18) from impact, such protection means (20) covering at least the upper part of the riser (18), the protecting means
10 (20) further being provided with a stretching or tensioning means (22), preferably attached to the lower end of the protection means (20).
2. A flexible riser or loading system according to claim 1, wherein the riser protection means (20) is suspended
15 from the vessel (10).
3. A flexible riser or loading system according to claim 1, wherein the riser protection means (20) is suspended
20 from a submerged turret loading buoy (19).
4. A flexible riser or loading system according to any one of the claims 1-3, wherein the stretching means (22) is formed by an annular body (22) surrounding the flexible
25 riser (18).
5. A flexible riser or loading system according to any one of the claims 1-4, wherein the stretching means (22) is moored to the sea bed (16) by means of wires (30).
30
6. A flexible riser or loading system according to any one of the claims 1-5, wherein the stretching means (22) at the lower end of its interior surface is provided with a curced surface designed to reduce detrimental impact or
35 wear and tear on the riser caused by relative movement of the stretching means (22).

7. A flexible riser or loading system according to any one of the claims 1-5, wherein the riser (18) in the vicinity of the stretching means (22) is provided with a collar (27) designed to reduce detrimental impact on the riser caused by relative movement of the stretching means (22).

8. A flexible riser or loading system according to claim 1, wherein the stretching means (22) are suspended by means of chains or wires (21) carrying the riser protection.

9. A flexible riser or loading system according to any one of the claims 1-8, wherein the riser protection (20) is formed by a plurality of separate hollow elements (23), each being suspended by means of chains or lines (21).

10. A flexible riser or loading system according to claim 9, wherein the hollow elements (23) are truncated and conical with a smaller upper diameter and a larger lower diameter or vice versa.

11. A flexible riser or loading system according to any one of the claims 9 or 10, wherein the hollow elements (23) forming the riser protection means (20) are stacked on top of each other when in a retracted position.

12. A flexible riser or loading system according to any one of the claims 1-11, wherein the riser protection means (20) is completely retractable into a sheltered position on the vessel (10).

13. A flexible riser or loading system according to any one of the claims 1-12, wherein the hollow elements (23) are provided with internally coating or friction reducing layer in order to minimize friction or load impact between the riser (18) and the protection means (20), enabling the

riser (18) to move freely within the riser protection means (20).

- 5 14. A flexible riser or loading system according to any one of the claims 1-13, wherein each hollow element (23) at its wider edge, is provided with a stacking ridge (25) enabling the hollow element (23) to be stacked on a next element (23).




FIG. 1




FIG. 2

2/5

10/540507




FIG. 3




FIG. 4




FIG. 5




FIG. 6

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 2003/000378

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: E21B 17/01, E02B 17/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: E21B, E02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4505618 A (N. YASHIMA), 19 March 1985 (19.03.1985)	1-2
A	--	3-14
A	US 3370432 A (R.M. BUTLER ET AL), 27 February 1968 (27.02.1968)	1-14
A	US 4063428 A (H. WAAS), 20 December 1977 (20.12.1977)	1-14

☐ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

* Special categories of cited documents

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

9 February 2004

Date of mailing of the international search report

10 -02- 2004

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Christer Bäcknert / MRo

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

24/12/2003

International application No.

PCT/NO 2003/000378

US	4505618	A	19/03/1985	CA	1197183	A	26/11/1985
				FI	831402	A	23/04/1984
				FI	883687	A	08/08/1988
				JP	1694716	C	17/09/1992
				JP	3058718	B	06/09/1991
				JP	59159793	A	10/09/1984
				NO	831427	A	24/04/1984
				NO	863035	A	24/04/1984
				JP	59050890	A	24/03/1984

US	3370432	A	27/02/1968	NONE			
----	---------	---	------------	------	--	--	--

US	4063428	A	20/12/1977	CA	1050287	A	13/03/1979
				DE	2537918	A,B,C	10/03/1977
				DE	2636334	A	16/02/1978
				JP	53021801	A	28/02/1978
				NO	147921	B,C	28/03/1983
				NO	772824	A	14/02/1978
